

# ColorBurst Powercore gen2, RGBA

Architectural and landscape LED spotlight with intelligent color light

Date: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Firm Name: \_\_\_\_\_  
 Project: \_\_\_\_\_

ColorBurst Powercore gen2 is a high-output, exterior-rated LED lighting luminaire designed for accent and site lighting. Standard format Architectural and Landscape luminaires deliver full-color light output of up to 1,151 lumens to support a range of dynamic uplighting, floodlighting, and decorative lighting applications.

- Expands customization with a wide range of new accessory options. In addition to the native 8° lens, six different spread lenses can customize the luminaire to produce 10°, 20°, 40°, 60°, 80°, and 10° x 40° (asymmetric) beam angles. Four housing color choices (black, gray, white, and bronze)—plus the option to add a louver, full glare shield, and half glare shield—create new aesthetic possibilities for designers and architects.
- Improves color consistency between all LED luminaires in a family with Chromasync technology. During the manufacturing process a calibrated light measurement device creates an algorithm to define a common color gamut for an entire family of LED luminaires. When Chromasync is enabled, color consistency between luminaires is achieved without having to manually adjust color points on each luminaire.
- Complies with ASTM B117 corrosion resistance standard for > 1,500 hours.



[Product page](#)

Beam Angle	8°, 10°, 20°, 40°, 60°, 80°, 10° x 40°
Lumens*	979 to 1,151
Efficacy (lm/W) All Channels Full On	31 to 36
LED Channels	Red/Green/Blue/Amber

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz
Power Consumption	33 W
Weight	3.5 kg (7.7 lb) Landscape 5.5 kg (12.1 lb) Architectural
Housing Material	Die-cast aluminium, powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, RCM
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

## 8° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC
<a href="#">RGBA, 8° Native (no spread lens), Black Housing, Landscape</a>	8°	1,151	36	423-000005-23	912400135487
<a href="#">RGBA, 8° Native (no spread lens), Bronze Housing, Landscape</a>	8°	1,151	36	423-000005-29	912400135491
<a href="#">RGBA, 8° Native (no spread lens), Gray Housing, Landscape</a>	8°	1,151	36	423-000005-20	912400135485
<a href="#">RGBA, 8° Native (no spread lens), White Housing, Landscape</a>	8°	1,151	36	423-000005-26	912400135489
<a href="#">RGBA, 8° Native (no spread lens), Black Housing, Architectural</a>	8°	1,151	36	423-000005-24	912400135488
<a href="#">RGBA, 8° Native (no spread lens), Bronze Housing, Architectural</a>	8°	1,151	36	423-000005-30	912400135492
<a href="#">RGBA, 8° Native (no spread lens), Gray Housing, Architectural</a>	8°	1,151	36	423-000005-21	912400135486
<a href="#">RGBA, 8° Native (no spread lens), White Housing, Architectural</a>	8°	1,151	36	423-000005-27	912400135490



## 10° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 10° Spread Lens, Black Housing, Landscape</a>	10°	1,007	31.4	423-000005-23	912400135487	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, Bronze Housing, Landscape</a>	10°	1,007	31.4	423-000005-29	912400135491	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, Gray Housing, Landscape</a>	10°	1,007	31.4	423-000005-20	912400135485	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, White Housing, Landscape</a>	10°	1,007	31.4	423-000005-26	912400135489	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, Black Housing, Architectural</a>	10°	1,007	31.4	423-000005-24	912400135488	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, Bronze Housing, Architectural</a>	10°	1,007	31.4	423-000005-30	912400135492	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, Gray Housing, Architectural</a>	10°	1,007	31.4	423-000005-21	912400135486	120-000189-18	912400135371
<a href="#">RGBA, 10° Spread Lens, White Housing, Architectural</a>	10°	1,007	31.4	423-000005-27	912400135490	120-000189-18	912400135371

## 20° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 20° Spread Lens, Black Housing, Landscape</a>	20°	990	31	423-000005-23	912400135487	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, Bronze Housing, Landscape</a>	20°	990	31	423-000005-29	912400135491	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, Gray Housing, Landscape</a>	20°	990	31	423-000005-20	912400135485	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, White Housing, Landscape</a>	20°	990	31	423-000005-26	912400135489	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, Black Housing, Architectural</a>	20°	990	31	423-000005-24	912400135488	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, Bronze Housing, Architectural</a>	20°	990	31	423-000005-30	912400135492	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, Gray Housing, Architectural</a>	20°	990	31	423-000005-21	912400135486	120-000189-12	912400133442
<a href="#">RGBA, 20° Spread Lens, White Housing, Architectural</a>	20°	990	31	423-000005-27	912400135490	120-000189-12	912400133442

## 40° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 40° Spread Lens, Black Housing, Landscape</a>	40°	1,004	31	423-000005-23	912400135487	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, Bronze Housing, Landscape</a>	40°	1,004	31	423-000005-29	912400135491	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, Gray Housing, Landscape</a>	40°	1,004	31	423-000005-20	912400135485	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, White Housing, Landscape</a>	40°	1,004	31	423-000005-26	912400135489	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, Black Housing, Architectural</a>	40°	1,004	31	423-000005-24	912400135488	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, Bronze Housing, Architectural</a>	40°	1,004	31	423-000005-30	912400135492	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, Gray Housing, Architectural</a>	40°	1,004	31	423-000005-21	912400135486	120-000189-13	912400133443
<a href="#">RGBA, 40° Spread Lens, White Housing, Architectural</a>	40°	1,004	31	423-000005-27	912400135490	120-000189-13	912400133443

## 60° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 60° Spread Lens, Black Housing, Landscape</a>	60°	991	31	423-000005-23	912400135487	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, Bronze Housing, Landscape</a>	60°	991	31	423-000005-29	912400135491	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, Gray Housing, Landscape</a>	60°	991	31	423-000005-20	912400135485	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, White Housing, Landscape</a>	60°	991	31	423-000005-26	912400135489	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, Black Housing, Architectural</a>	60°	991	31	423-000005-24	912400135488	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, Bronze Housing, Architectural</a>	60°	991	31	423-000005-30	912400135492	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, Gray Housing, Architectural</a>	60°	991	31	423-000005-21	912400135486	120-000189-14	912400133444
<a href="#">RGBA, 60° Spread Lens, White Housing, Architectural</a>	60°	991	31	423-000005-27	912400135490	120-000189-14	912400133444

## 80° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 80° Spread Lens, Black Housing, Landscape</a>	80°	979	31	423-000005-23	912400135487	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, Bronze Housing, Landscape</a>	80°	979	31	423-000005-29	912400135491	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, Gray Housing, Landscape</a>	80°	979	31	423-000005-20	912400135485	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, White Housing, Landscape</a>	80°	979	31	423-000005-26	912400135489	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, Black Housing, Architectural</a>	80°	979	31	423-000005-24	912400135488	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, Bronze Housing, Architectural</a>	80°	979	31	423-000005-30	912400135492	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, Gray Housing, Architectural</a>	80°	979	31	423-000005-21	912400135486	120-000189-15	912400133445
<a href="#">RGBA, 80° Spread Lens, White Housing, Architectural</a>	80°	979	31	423-000005-27	912400135490	120-000189-15	912400133445

## 10° x 40° Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Black Housing, Landscape</a>	10° x 40°	1,014	31.7	423-000005-23	912400135487	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Bronze Housing, Landscape</a>	10° x 40°	1,014	31.7	423-000005-29	912400135491	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Gray Housing, Landscape</a>	10° x 40°	1,014	31.7	423-000005-20	912400135485	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, White Housing, Landscape</a>	10° x 40°	1,014	31.7	423-000005-26	912400135489	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Black Housing, Architectural</a>	10° x 40°	1,014	31.7	423-000005-24	912400135488	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Bronze Housing, Architectural</a>	10° x 40°	1,014	31.7	423-000005-30	912400135492	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, Gray Housing, Architectural</a>	10° x 40°	1,014	31.7	423-000005-21	912400135486	120-000189-16	912400133446
<a href="#">RGBA, 10° x 40° Asymmetric Spread Lens, White Housing, Architectural</a>	10° x 40°	1,014	31.7	423-000005-27	912400135490	120-000189-16	912400133446

\* Lumen output measurements comply with IES LM-79-08 testing procedures.

† Trim Ring or Glare Shield required for mounting spread lens. Must be ordered separately.

