

Vaya Flood MP G2 White

Mid power architectural LED flood light for crisp white lighting effects

Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

Vaya Flood MP (gen2) is a reliable and cost effective LED flood lighting solution for both exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.



- Powerful - Throwing light with 10lx up to 89 m / 1fc up to 292 ft high, this narrow beam luminaire is a powerful solution for any size of project.
- Compact - Unlike other flood lighting solutions, the Vaya Flood series are compact sized & light-weight luminaires, that combine an aluminium die-cast housing which is both anodized and powder coated to protect against corrosion, tempered glass, pressure equalizing air vents and IP66 outdoor rating, making the product robust against harsh outdoor environments.

[Product page](#)

Beam Angle	10°, 20°, 40°
Lumens*	5,180 to 6.312
Efficacy	76.3 to 93.3
CRI @ 3000 K†	80
CRI @ 4000 K†	82
Color Temperature [§]	3000 K, 4000 K

Input Voltage	120 to 277 VAC, 50/60 Hz and 220 to 240 VAC, 50/60 Hz
Power Consumption	68 W
Weight	5.72 kg (12.61 lb)
Housing Material	Die-cast aluminium, dark grey powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, CQC, RCM
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

3000 K Specification Sheets

Custom products information available

PDF Download	Beam Angle	Lumens*	Efficacy	CRI†	Item Number	12 NC
3000 K, 10°, CE/CQC	10°	5,773	84.6	80	350-000016-00	912400134020
3000 K, 10°, UL	10°	5,773	84.6	80	350-000016-16	912400134026
3000 K, 20°, CE/CQC	20°	5,660	83.5	80	350-000016-01	912400134021
3000 K, 20°, UL	20°	5,660	83.5	80	350-000016-17	912400134027
3000 K, 40°, CE/CQC	40°	5,180	76.3	80	350-000016-02	912400134022
3000 K, 40°, UL	40°	5,180	76.3	80	350-000016-18	912400134028

COLOR KINETICS
 vaya series

4000 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	CRI [†]	Item Number	12 NC
4000 K, 10°, CE/CQC	10°	6,312	93.3	82	350-000016-08	912400134023
4000 K, 10°, UL	10°	6,312	93.3	82	350-000016-24	912400134029
4000 K, 20°, CE/CQC	20°	6,150	90.8	82	350-000016-09	912400134024
4000 K, 20°, UL	20°	6,150	90.8	82	350-000016-25	912400134030
4000 K, 40°, CE/CQC	40°	5,634	83.3	82	350-000016-10	912400134025
4000 K, 40°, UL	40°	5,634	83.3	82	350-000016-26	912400134031

* Lumen output measurements comply with IES LM-79-08 testing procedures.

[‡] Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

[†] CRI refers to CRI Ra value, CRI R9 refers to R9 value in accordance with IESNA LM-79 standards.

COLORKINETICS vaya series

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/vaya